



Aluminium / Stainless Steel A2/A3 Dome Head -open-

according to DIN EN ISO 15977

d	l+1		dk	k	dm	No.	
2,4	4,0	0,5 – 2,0	5,0 -0,7	0,55 ± 0,15	1,5	10.702.024.040	500
	6,0	1,5 – 4,0				10.702.024.060	500
	8,0	3,5 – 6,0				10.702.024.080	500

EN AW - 5019 [AlMg5] 2,5 mm 380 N 600 N

d	l+1		dk	k	dm	No.	
3,0	4,0	0,5 – 2,0	6,3 -0,7	0,8 ± 0,2	1,7	10.702.030.040	500
	6,0	1,5 – 4,0				10.702.030.060	500
	8,0	3,0 – 6,0				10.702.030.080	500
	10,0	5,0 – 7,5				10.702.030.100	500
	12,0	7,0 – 9,0				10.702.030.120	500

EN AW - 5019 [AlMg5] 3,1 mm 660 N 900 N

d	l+1		dk	k	dm	No.	
3,2	6,0	1,5 – 3,5	6,5 -0,7	0,8 ± 0,2	1,9	10.702.032.060	500
	8,0	3,0 – 5,5				10.702.032.080	500
	10,0	5,0 – 7,5				10.702.032.100	500
	12,0	7,0 – 9,0				10.702.032.120	500

EN AW - 5019 [AlMg5] 3,3 mm 660 N 1100 N

d	l+1		dk	k	dm	No.	
4,0	5,0	0,5 – 2,5	8,0 -1,0	1,0 ± 0,3	2,0	10.702.040.050	500
	6,0	1,0 – 3,5				10.702.040.060	500
	7,0	3,0 – 4,5				10.702.040.070	500
	8,0	3,0 – 5,5				10.702.040.080	500
	10,0	5,0 – 7,0				10.702.040.100	500
	12,0	6,5 – 9,0				10.702.040.120	500
	16,0	8,5 – 12,5				10.702.040.160	500
	18,0	12,0 – 14,5				10.702.040.180	500
	20,0	12,5 – 16,5				10.702.040.200	500

EN AW - 5057 [AlMg3] 4,1 mm 1120 N 1420 N

d	l+1		dk	k	dm	No.	
4,8	6,0	1,0 – 3,0	9,5 -1,0	1,1 ± 0,3	2,7	10.702.048.060	500
	8,0	1,0 – 5,0				10.702.048.080	500
	10,0	4,0 – 6,5				10.702.048.100	500
	12,0	6,0 – 8,0				10.702.048.120	500
	14,0	7,5 – 10,0				10.702.048.140	500
	16,0	8,0 – 12,0				10.702.048.160	500

EN AW - 5754 [AlMg3] 4,9 mm 1480 N 1950 N

d	l+1		dk	k	dm	No.	
5,0	6,0	1,0 – 3,0	9,5 -0,8	1,1 ± 0,3	2,7	10.702.050.060	500
	8,0	2,5 – 5,0				10.702.050.080	500
	10,0	4,0 – 6,5				10.702.050.100	500
	12,0	6,0 – 8,0				10.702.050.120	500
	14,0	7,5 – 10,0				10.702.050.140	500
	16,0	8,0 – 12,0				10.702.050.160	500
	18,0	11,5 – 13,5				10.702.050.180	500
	20,0	12,0 – 15,5				10.702.050.200	500
	25,0	15,0 – 20,5				10.702.050.250	500
	30,0	20,0 – 25,0				10.702.050.300	500

EN AW - 5754 [AlMg3] 5,1 mm 1650 N 2000 N

d	l+1		dk	k	dm	No.	
6,0	10,0	3,0 – 5,5	12,0 -1,2	1,5 ± 0,4	3,2	10.702.060.100	500
	12,0	5,0 – 7,5				10.702.060.120	500
	16,0	7,0 – 11,0				10.702.060.160	500
	18,0	10,5 – 13,0				10.702.060.180	500

EN AW - 5754 [AlMg3] 6,1 mm 2520 N 2850 N

