



The flexible NEOPREN blind nuts offer a lot of advantages for different kinds of applications.

- no special tool necessary
- vibration-isolating
- suitable for connections between different kinds of materials
- good machining in irregular bore holes
- non-conductive
- corrosion- and ozone resistant
- detachable
- noise repressing



These fasteners are used for example in automotive, furniture or electronic industries in large quantities.

Neopren Blind Nut

2<sup>4</sup>







## Neopren Blind Nut



**NEOPREN**  
with thread insert  
made of brass

M		D	dk	l	k	Nm	Shore A	Nr.	
<b>M3</b>	0,4 – 4,0	7,9	11,0	12,6	1,2	0,25 - 0,5	60	10.890.030.400	500
<b>M4</b>	0,4 – 4,0	7,9	11,0	12,6	1,2	0,25 - 0,5	70	10.890.040.400	500
8,0 mm									
<b>M5</b>	0,4 – 4,9	9,6	12,7	14,1	0,9	0,35 - 0,5	70	10.890.050.500	500
	4,0 – 11,6		14,0	21,5		0,3 - 0,9		10.890.050.116	
	7,9 – 16,0		14,0	26,5	1,3	0,3 - 0,7		10.890.050.160	
	20,5 – 30,0		14,0	39,0		0,6 - 1,0		10.890.050.300	
9,7 mm									
<b>M6</b>	0,4 – 2,8	12,7	16,0	16,0	1,3	0,6 - 1,0	60	10.890.060.300	500
	0,8 – 4,7		19,0	21,1	4,75	0,8 - 1,0	70	10.890.060.500	
	6,4 – 11,5		16,3	26,7	2,0	0,8 - 1,0	10.890.060.115		
12,8 mm									
<b>M8</b>	0,4 – 4,0	15,9	22,1	18,3	3,2	1,0 - 1,5	60	10.890.080.400	250
	3,9 – 9,5		22,1	27,9	5,7	1,0 - 1,6		10.890.080.950	100
16,0 mm									

### Capabilities



Low-vibration and detachable connections.

Assembly in irregular blind holes.